

*Матеріали ХLI-ої Міжнародної науково-практичної конференції
(07 лютого 2024 року, м. Анкара (Туреччина), дистанційно)*

Smetankina N.,
Doctor of Technical Sciences,
Head of Department of Vibration and
Thermostability Studies,
*Anatolii Pidgorny Institute of
Mechanical Engineering Problems of the
National Academy of Sciences of Ukraine
Kharkiv, Ukraine*

Misiura S.,
Candidate of Technical Sciences,
Senior Researcher of Vibration and
Thermostability Studies,
*Anatolii Pidgorny Institute of
Mechanical Engineering Problems of the
National Academy of Sciences of Ukraine
Kharkiv, Ukraine*

Misiura Ie.,
Candidate of Technical Sciences,
Associate Professor of Department of
Higher Mathematics, Economic and
Mathematical Methods,
*Simon Kuznets Kharkiv National
University of Economics,
Kharkiv, Ukraine*

**MATHEMATICAL MODELING AND
OPTIMIZATION OF THERMAL STRESSED STATE
OF SHELL STRUCTURES IN POWER
ENGINEERING**

At present, power engineering is one of the priority industries [1-3]. Modern requirements to operational reliability and durability



of power engineering facilities cause the need for both modernizations of existing equipment and development of new structures from advanced materials with enhanced performance properties [3-5]. Manufacturing of many elements of such structures, as a rule, is associated with technologies characterized by operations with high temperature conditions [6, 7]. Structural transformations of materials due to intensive thermal effects lead to the emergence of inhomogeneous high-gradient thermal stress states in the areas of technological influence [8, 9]. Thus, the development of methods for research and optimization of high-gradient thermal stress states of critical elements of power engineering structures taking into account the peculiarities of manufacturing processes is an urgent task. The most widespread structures of power engineering include shell-type structures, among which we can distinguish: fuel elements of nuclear engineering, pressure vessels of power apparatuses, hull structures of power plants, parts and units of technological equipment of metallurgical production. Typical for them is a complex structural form consisting of many articulated shell elements: shells, spherical bottoms, nozzles, fittings, pipelines, etc. [10-12]. The presence of unbreakable joint and mating parts significantly affects the strength and load-bearing capacity of the whole product.

From a large number of varieties of connections of separate units into a single structural form, welded joints formed by longitudinal, circular, meridional and many contour welds are widespread. Technological processes of their manufacturing are characterized by local inhomogeneous high-gradient thermal loading, volumetric deformation of metal in the zone of influence, concentration of elastic-plastic stresses in the vicinity of the welded joint, contributing to the formation of technological defects in the form of cracks and shrinkage porosity. The combination of



negative factors of technological character and design features in certain conditions can lead to a decrease in operational properties and possible subsequent destruction of the structure.

It should be emphasized that technological processes of power engineering associated with high-temperature loading, such as welding, heat treatment, induction heating, are currently the main ones in the manufacture of load-bearing shell structures of power plants, the strength reliability of which significantly depends on the residual stress state. Concentration of local tensile thermal stresses in the joints of the mold contributes to the development of cracks during operation and can lead to loss of stability. The stringent requirements for such structures include, among other issues, ensuring minimum temperature deformations, dimensional stability and accuracy of fabrication of the main load-bearing elements. When the resources of optimal design are exhausted, manufacturing techniques that produce elastic-plastic deformations become of paramount importance in the creation of high-quality power equipment. To reduce dangerous levels of thermal stresses and deformations, it is necessary to develop methods for optimization of thermal stress states taking into account the choice of quality criteria, constraints and target function [11, 12].

The aim of the work is to develop adequate models and methods of research and optimization of high-gradient thermal stressed states of articulated shell-type structures taking into account the peculiarities of technological processes of power engineering.

Mathematical models for determining the parameters of the thermal stressed state of articulated structures of complex geometric shape with variable physical and mechanical properties experiencing local high-gradient thermal loading are developed.



Algorithms for optimization of thermal stressed states of articulated shell-type structures on the basis of the system of quality criteria, selection of the optimal design form and optimal control of the parameters of technological manufacturing processes have been developed. Structures of estimation weight functions is mathematically justified. The results of the study can be applied in the development of advanced power structures with enhanced performance properties.

References:

1. Sierikova O., Strelnikova E., Gnitko V., Degtyarev K. Boundary calculation models for elastic properties clarification of three-dimensional nanocomposites based on the combination of finite and boundary element methods. In: 2021 IEEE 2nd KhPI Week on Advanced Technology (KhPIWeek). 2021. P. 351–356.
2. Шупиков А.Н., Бузько Я.П., Сметанкина Н.В., Угримов С.В. Нестационарные колебания многослойных пластин и оболочек и их оптимизация. Харьков: ХНЭУ, 2004. 252 с.
3. Кантор Б.Я., Андриющенко С.А., Мисюра С.Ю. Исследование напряженно-деформированного состояния крышки гидротурбины и возможностей совершенствования ее конструкции. Вісник НТУ «ХП». Серія: Динаміка і міцність машин. 2010. № 69. С. 58–66.
4. Шупиков А.Н., Мисюра С.Ю., Ярещенко В.Г. Численное и экспериментальное исследование гидроупругих колебаний оболочек. Восточно-Европейский журнал передовых технологий. 2014. № 6(7). С. 8–12.
5. Сметанкина Н.В., Мисюра С.Ю., Линник А.В. Влияние предварительно напряженного состояния на частоты несущих конструкций гидротурбин. Вісник НТУ «ХП». Серія: Динаміка і міцність машин. 2018. Т. 1, № 38. С. 42–48.



6. Smetankina N., Merkulova A., Merkulov D., Misura S., Misiura Ie. Modelling thermal stresses in laminated aircraft elements of a complex form with account of heat sources. ICoRSE 2022. Lecture Notes in Networks and Systems. 2023. Vol. 534. Springer, Cham. P. 233–246.

7. Malykhina A. I., Merkulov D. O., Postnyi O. V., Smetankina N. V. Stationary problem of heat conductivity for complex-shape multilayer plates. Bulletin of V.N. Karazin Kharkiv National University. Series “Mathematical modeling. Information technology. Automated control system”. 2019. Vol. 41. P. 46–54.

8. Smetankina N.V., Postnyi O.V., Merkulova A.I., Merkulov D.O. Modeling of non-stationary temperature fields in multilayer shells with film heat sources. In: 2020 IEEE KhPI Week on Advanced Technology (KhPIWeek). 2020. P. 242–246

9. Smetankina N., Ugrimov S., Kravchenko I., Ivchenko D. Simulating the process of a bird striking a rigid target. Advances in Design, Simulation and Manufacturing II. DSMIE 2019. Lecture Notes in Mechanical Engineering. Springer, Cham, 2020. P. 711–721.

10. Smetankina N., Postnyi O. Nonstationary heat conduction in multilayer glazing subjected to distributed sources. Informatyka, Automatyka, Pomiarы w Gospodarce i Ochronie Środowiska. 2020. Vol. 10, No 2. P. 28–31.

11. Smetankina N., Semenets O., Merkulova A., Merkulov D., Misura S. Two-stage optimization of laminated composite elements with minimal mass. Smart Technologies in Urban Engineering. STUE-2022. Lecture Notes in Networks and Systems. Springer, Cham, 2023. Vol. 536. P. 456–465.

12. Smetankina N.V., Postnyi O.V., Misura S.Yu., Merkulova A.I., Merkulov D.O. Optimal design of layered cylindrical shells with minimum weight under impulse loading. In: 2021 IEEE 2nd KhPI Week on Advanced Technology (KhPIWeek). 2021. P. 506–509.

